



36V 105AH LITHIUM BATTERY

General Information

Model Number:	BL-36V105A
Chemistry:	Lithium Iron Phosphate (LiFePO ₄)
Nominal Voltage:	38.4V
Nominal Capacity:	105Ah
Energy:	4.032kWh
Cycle Life:	≥3500 cycles @100% DOD ≥6000 cycles @50% DOD

Electrical Specifications

Nominal Voltage:	38.4V (3.2V per cell × 12)
Operating Voltage Range:	30V – 43.8V
Nominal Capacity:	105Ah
Standard Charge Current:	30A
Max Continuous Charge Current:	100A
Max Continuous Discharge Current:	200A
Peak Discharge Current:	300A (30s) 600A (3s)
Charge Cut-off Voltage:	43.8V
Discharge Cut-off Voltage:	30V
Internal Resistance:	≤30mΩ
Self-Discharge Rate:	≤3%/Month

Mechanical Specifications

Dimensions (L×W×H):	12.99 in × 10 in × 10.43 in
Weight:	≈80.5 lbs
Case Material:	• Proprietary, Corrosion Resistant Steel • IP67 Waterproofing

Environmental Conditions

Charge Temperature Range:	32° ~ 131°F
Discharge Temperature Range:	-4° ~ 140°F
Storage Temperature Range:	50° ~ 113°F
Relative Humidity:	≤75% RH



Battery Management System (BMS)

Overcharge Protection:	Yes
Over-Discharge Protection:	Yes
Over-Current Protection:	Yes
Short Circuit Protection:	Yes
Cell Balancing:	Active/Passive balance

Safety & Certifications


Certifications:	• Shipping Safety • International/EU Compliance • Battery Safety • Material Safety Data • Performance & Industrial Safety • Chemical/Environmental Safety
Communication:	Bluetooth
Warranty:	10 year Transferable Warranty

	• UN38.3 + Sea & Air Transport Reports • CB & CE • UL1973 & UL2580 • MSDS • IEC626660 & IEC62619 • REACH & RoHS
--	---

Cycle Life Performance

Cycle Life	≥3500 cycles, 1C @ DOD 100% ≥6000 cycles, 0.2C @ DOD 100%
------------	--

Dimesional Specifications



Never use or keep the battery under the high temperature. Otherwise it will cause battery heat, get into fire or lose some function and reduce the life. The proposed temperature for long-term storage is 0–45°C.