

MINIMUM REQUIREMENTS

1



12 HP DC TO AC MOTOR CONVERSION KIT

KIT PART # PK-000052

**THE FOLLOWING ITEMS ARE REQUIRED
BEFORE THIS KIT CAN BE INSTALLED!**

VEHICLE MAKE	MODEL	YEAR START	YEAR END	NOTE
E-Z-GO®	TXT®	1996	PRESENT	
REQUIREMENTS	ITEM			NOTE
VEHICLE CONTROLLER	CURTIS® 1206HB- (Original Stock Controller)			
MOTOR TYPE	48V DC MOTOR (Original Stock Motor)			Does not fit TXT 36V DC Cart.
AXLE	Transaxle w/ 19 Spline (Original Stock Axle on DC Cart)			
HEAVY DUTY SOLENOID W/ PRE-CHARGE RESISTOR	Heavy Duty Solenoid & Pre-Charge Resistor rated for 400 amp.			Required when driving at higher speeds or hilly terrain for longer periods of time.
BATTERY	48V Lead Acid			In New or Good condition
	48V- 72V Lithium Ion w/a rating of at least:	Continuous Discharge 100A	Maximum Discharge 250A (5 seconds)	The Batteries can not have a Nominal state of over 72v.
2GA CABLES	2GA Power Cables between Motor, Controller and Battery.			Can be ordered from the dealer or at SilverWolf.com . Part # PK-000011 (Sold Separately)
THROTTLE	Original OEM Stock ITS Throttle			Do not use a non-OEM Throttle.